

Putzgrund 610



Technical data

| | |
|-----------------|------------------------|
| Specific use(s) | first coat |
| Density | 1,61 g/cm ³ |
| Consumption | 350 ml/m ² |

Components

| | |
|--------------------------------------|-------------------------|
| Product Code/GISCODE | M-GP01 |
| Declaration of ingredients | Emulsion paint, aqueous |
| preservatives | not contained |
| VOC content in accordance with | 0 % |
| Directive 2004/42/EC | < 1 g/l |
| VOC content LEED [less water] | < 1 g/l |
| Solvent and plasticiser-free in | yes |
| accordance with VdL- RL 01 | |
| Water-dilutable in accordance with | yes |
| 2004/42/EC (Decopaint) | |
| Lead, cadmium, chromium VI * | not contained |
| (* not contained in the formulation) | |

Environmental labels

Building certifications

Suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

| No. | Application site | Product type | QS 1 | QS 2 | QS 3 | QS 4 |
|-----|---|---|------|------|------|------|
| 3 | Liquid coating materials for outdoor mineral surfaces. E.g. concrete, masonry, mineral mortar and filler, plaster, ETICS | Decorative paints | yes | yes | yes | yes |
| 27 | Factory-coated components, e.g. façade elements, doors, radiators, etc. Galvanising is not considered coating under this criterion. | Primer and top coating (e.g. paints, varnishes) | yes | yes | yes | yes |

| | | |
|---|---|-----------------------------|
| Suitability for use in accordance with LEED | Category (IEQ4.2 - 2009) | primer, sealer or undercoat |
| | VOC limit | 100 g/l |
| | Limit fulfilled | yes |
| Recycling share | not contained | |
| Production site | DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt | |